

Rustilo™ 5905

Neat corrosion preventive fluid

Description

Castrol Rustilo™ 5905 (previously called Castrol Product 5905) is a neat corrosion preventive fluid, consisting of a blend of vegetable oil, alcohols and additives.

Application

Rustilo 5905 has been designed for use as an assembly fluid and has been specially formulated to give corrosion protection to brake and clutch hydraulic units whilst kept in storage.

Advantages

- Residual film is compatible with brake fluid.
- Compatible with steel, grey cast iron, aluminium and copper.
- Compatible with elastomers, such as SBR and EPDM.
- Heavy metals free, (example Barium) which may help you to fulfil aspects of legislative requirements and waste treatment requirements that specify that these chemicals are excluded.

Typical Characteristics

Name	Method	Units	Value
Appearance	Visual	-	Red, clear and bright liquid
Density @ 15°C / 59°F	ASTM D4052 / ISO 12185	g/ml	0.96
Viscosity @ 40°C	ASTM D 445 / ISO 3104	mm ² /s	56
Flash Point	EN 22719	°C	65
Water Content	ASTM D1123	%	< 0.5
pH	SAE J 1703	-	6
ERBP (Equilibrium Reflux Boiling Point)	ASTM D1120	°C	> 150
Film Thickness	-	µm	5
Multiple Strip Corrosion Test	TS 2-32-01	-	Pass
Elastomer Compatibility (72 hrs @ 70 °C)	TS 2-32-01	%	0 - 9

Subject to usual manufacturing tolerances.

User Advice

Rustilo 5905 is not to be used as a working fluid in a brake or clutch system (i.e. as a brake fluid).

Additional Information

The claims on film thickness and consumption are average values. These are valid for smooth surfaces with good drain-off characteristics and simple geometries without holes or recesses.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer to the product safety data sheet

This product was previously called Product 5905. The name was changed in 2015.

Rustilo™ 5905

10 Feb 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial